

(Reference) Norm ULC S515-13

14.9.2.4 REFERENCE 15.9.3 IN NFPA 1901-09

The perimeter of the fire fighting apparatus shall have a retroreflective stripe(s) affixed to it.

14.9.2.5 The stripe or combination of stripes is to be a minimum of 100 mm (4 in) in total width and shall conform to the minimum requirements of CGSB 62-GP-11M, Marking Material, Retroreflective, Enclosed Lens, Adhesive Backing, or ASTM D 4956, Standard Specification for Retroreflective Sheeting for Traffic Control, Type I, Class 1 or Class 3.

14.9.2.6 The retroreflective material shall be affixed to at least 50 % of the cab and body length on each side, excluding pump panel areas, and at least 25 % of the width of the front of the fire fighting apparatus.

14.9.2.7 At least 50 % of the rear-facing vertical surfaces, visible from the rear of the fire fighting apparatus, excluding any pump panel areas not covered by a door, shall be equipped with retroreflective striping in a chevron pattern sloping downward and away from the centerline of the vehicle at an angle of 45°.

14.9.2.7.1 Each stripe shall be 150 mm (6 in) in width.

14.9.2.8 All or part of the required striping material is permitted to have a graphic design meeting the retroreflectivity requirements of Clause 14.9.2.5, if the design or combination thereof covers at least the same perimeter length(s) requirement.